









XD-125

Commercial Dehumidifier

The XPOWER XD-125 Commercial Dehumidifier is designed to maximize water extraction while combining the highest efficiency in performance and portability. A highly durable housing construction can withstand rough handling, while its semi-pneumatic wheels allow for easy transport and maneuverability on the job site. With the XD-125's unique and complete operating features, it is the perfect machine for not only water damage restoration jobs, but also for multiple industrial applications where maximum performance in air drying is a necessity.

- A built-in water pump with drainage hose automatically purges when full- eliminating the task of monitoring collection tank levels
- Water removal capacity: 76 pints/day at AHAM (80°F, 60% RH); 125 Pints/Day (90°F, 90% RH)
- Uses standard refrigerant (R410A); with operation range between 33° – 100°F (1° – 38°C)
- 25 Ft. power cord and 20 Ft. long drain hose

SPECIFICATIONS

MODEL NO.	XD-125	
WATER REMOVAL CAPACITY	76 Pints/ Day @AHAM (80°F, 60% RH) 125 Pints/ Day (90° F, 90% RH)	
TYPE	Standard Refrigerant (R410A)	
VOLTS/HZ	115V/60Hz	
MOTOR	1HP	
AMP	7.3Amps	
RATED AIRFLOW	235 CFM	
SPEEDS	1 SPeed	
OPERATING RANGE	33° - 100° F (1° - 38°)	
FILTER	High Airflow Filter (HAF)	
WATER PUMP OUT	Centrifugal	
DRAIN HOSE LENGTH	20 Ft.	
COMPRESSOR TYPE	High Efficient Rotary Compressor	
UNIT WEIGHT	81 Lbs.	
UNIT DIMENSIONS (LxWxH)	20 x 19 x 32 in.	
CORD LENGTH	25 Ft.	
HOUSING	Roto Mold Polyethylene	
SAFETY CERTIFICATIONS	ETL/CETL	

MODEL NO.	X-3580
VOLTS/HERTZ	115V / 60Hz
MOTOR	1/2 HP
MAX AMP	2.8 A
RATED AIRFLOW	600 CFM
SPEEDS	5 Speed
CORD LENGTH	13 Ft.
DAISY CHAIN	No
STACKABLE	Yes
UNIT WEIGHT	32.8 Lbs.
UNIT DIMENSIONS (LXWXH)	19.6 x 12.3 x 21.6 in.
HOUSING	ABS
DUCT SIZE (AIR OUTLET DIMENSIONS) 5" x 10.8"
DUAL THERMAL PROTECTION	Yes
PALLET QUANTITY	18





