



Who We Are

XPOWER Manufacture Inc. brings over 25 years of experience developing an expanding series of products with the most advanced technology in today's market. By creating a fully integrated design with state-of-the art miniaturization, XPOWER's innovative inflatable products are lightweight and rugged – exactly what is required to serve two contrasting markets.

In partnership with its distributor network, XPOWER and its R & D engineers welcome new ideas and creative thinking to develop quality products for a profitable and long term relationship. XPOWER capitalizes on its global presence in its pursuit of enthusiastic and ambitious product distributors.

Precision Manufacturing

Designed with a spirit of innovation, XPOWER inflatable blowers appeal to both industry and consumers. Featuring highly efficient motors that produce extraordinarily strong airflow, XPOWER machines inflate quickly and effectively. A durable, streamlined and lightweight injection molded body symbolizes XPOWER's progressive design approach. Easy to carry and transport, XPOWER's inflatable blowers are built with the operator in mind.

Global Organization

XPOWER seeks to provide maximum value with a combination of superior product quality and service. A worldwide presence has created manufacturing for both 115V and 230V equipment for global distribution. US, direct import and OEM private label container orders enjoy prompt fulfillment from extensive inventory, thanks to world-class factory production capacity.

For product or parts assistance, XPOWER's customer service team offers comprehensive support for distributors and end users, assuring a first-class customer experience.

Industries Served

XPOWER designs and manufactures products that have become valuable tools in the inflatables, pet grooming, jan/san, restoration and DIY consumer markets.

Standards & Safety

XPOWER's thermally protected motors have globally recognized safety certifications, ensuring product safety. XPOWER controls and maintains the highest production standards in the industry, To assure you of our commitment to quality, all XPOWER products have a 1 year limited manufacturer's warranty.

2 www.xpower.com



TABLE OF CONTENTS

High Static Blowers

| - BR-2C01Apg 4 |
|---|
| - BR-201Apg 5 |
| - BR-232A, BR-252Apg 6 |
| - BR-282A, BR-292Apg 7 |
| Centrifugal Blowers |
| - P-800I, P-800HI, P-815I, P-830I, P-830HI pg 8 |
| Vertical Advertisement Blowers |
| - BR-18Lpg 9 |
| - BR-430, BR-430L, BR-440, BR-440L, BR-450, |
| BR-450L, BR-460, BR-460Lpg 10 |
| Air Pumps |
| - AP-1031A, AP-1131pg 11 |
| - AP-138A pg 12 |
| - AP-145Apg 13 |
| Specifications |























Perfect for home decorations and small inflatables, the **XPOWER BR-2C01A** inflatable blower is a lightweight and energy efficient blower. This unit's 1/8 HP motor draws minimum power and its durable housing endures tough usage. The BR-2C01A is designed to run continuously without racking up high electricity bills.

- Injection molded using durable high quality polypropylene
- Energy-efficient power usage of .8A
- ETL/CETL safety certified for indoor and outdoor use
- Lightweight for easy storage











- Polypropylene housing for durability
- Energy-efficient power usage
- ETL/CETL safety certified for indoor and outdoor use
- Easily transportable and lightweight













- Durable high quality polypropylene housing
- Under 10A power usage
- ETL/CETL safety certified
- Carrying handle for easy transportability















The **XPOWER BR-282A** and **BR-292A** are our most powerful inflatable blowers. Featuring 1-2 HP motors, they are ideal for large inflatable structures, advertisements, and a variety of other applications. The BR-282A is designed for both indoor and outdoor use and is ETL/CETL safety certified. Both are lightweight, making them easily transportable.


- The most powerful high static blowers in their class
- Injection molded using durable high quality polypropylene
- Carrying handle for easy transportability











- Clip-on adapter extends nozzle and features thick velcro loop band, ensuring secure attachment to a variety of inflatables.
- P-815l features sealed motor for outdoor performance
- ETL/CETL certified
















Create an attractive customizable light show with the XPOWER BR-18L LED air column blower. Compatible with 18" diameter inflatable pillars, the BR-18L is ideal for indoor use. Choose from several colors and effects including flashing, strobing and fading.

- Energy efficient 1/7 HP motor draws only .92 Amps
- Remote included
- Wide array of colors and transitions

BR-430, BR-430L, BR-440, BR-440L, BR-450L, BR-450L, BR-460L







- Powerful 1/3 (12") and 1 (18") HP motors
- Durable ABS construction
- Lightweight at 30 lbs and under









Much more powerful than battery powered pumps, the XPOWER AP-1031A and AP-1131 rapidly inflate air mattresses, pool toys and more. Plug the AC powered unit into a 110/120V outlet to generate 1.00 PSI for quick inflation and deflation; the DC unit plugs into a standard car cigarette lighter.

- UL/CUL safety certified (AP-1031A only)
- 3 valve adapters for compatibility with multiple inflatable types
- AC (outlet) and DC (car cigarette lighter) models available















Generating 1.5 PSI, the **XPOWER AP-138A** air pump can inflate air mattresses, swimming pools, water sport equipment, and more. Plug this AC powered unit into a 110/120V outlet for quick inflation and deflation. UL/CUL safety certified, this powerful pump features a 5' power cord.

- UL/CUL safety certified
- 2 valve adapters for compatibility with multiple inflatable types
- Able to inflate / deflate a wide variety of home and recreational inflatables







High Static Pressure

| MODEL NO. | BR-2C01A | BR-201A | BR-232A | BR-252A | BR-282A | BR-292A |
|----------------------|----------------|-------------------|------------------|-------------------|-------------------|-------------------|
| VOLTS/HERTZ | 120V/60Hz | 120V/60Hz | 120V/60Hz | 120V/60Hz | 120V/60Hz | 120V/60Hz |
| MOTOR | 1/8HP | 1/4HP | 1/2HP | 1HP | 2HP | 3HP |
| POWER | 0.8A | 2.2A | 5.5A | 9.8A | 12A | 18 A |
| RATED AIRFLOW | 120CFM | 250CFM | 600CFM | 1000CFM | 1500CFM | 1700CFM |
| SPEED | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE | SINGLE |
| CORD LENGTH | 6' | 6' | 6' | 6' | 12' | 12' |
| UNIT WEIGHT | 3.8lbs | 8lbs | 12lbs | 16.2lbs | 22lbs | 30.4lbs |
| UNIT DIMENSIONS | 8"x5.7"x8.5" | 12.6"x8.5"x12.6" | 15"x10.5"x15" | 15.5"x11.2"x16.7" | 18.5"x10.6"x19.9" | 18.5"X10.6"X19.9" |
| BOX WEIGHT | 4.5lbs | 9.6lbs | 14.2lbs | 18.6lbs | 25.8lbs | 33.3lbs |
| BOX DIMENSIONS | 8.7"x6.3"x9.4" | 13.6"x13.6"x10.4" | 15.8"x15.8"10.8" | 17.1"x17.1"x12.4" | 20"x18.5"x11.2" | 20"X18.5"X11.2" |
| SAFETY CERTIFICATION | UL/CUL | UL/CUL | UL/CUL | UL/CUL | UL/CUL | - |

Roof Top Blowers

| Model No. | P-800I | P-800HI | P-815I | P-830I | P-830HI |
|----------------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Volts/Hertz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz |
| Motor | 3/4HP | 3/4HP | 1 HP | 1HP | 1HP |
| Power | 7.5A | 7.5A | 8 A | 8.5A | 8.5A |
| Rated Airflow | 3200CFM | 3200CFM | 3600CFM | 3600CFM | 3600CFM |
| Speed | 3 SPEED | 3 SPEED | 1 SPEED | 3 SPEED | 3 SPEED |
| Cord Length | 20' | 20' | 20' | 20' | 20' |
| Unit Weight | 23lbs | 26lbs | 26.1lbs | 24lbs | 27lbs |
| Unit Dimensions | 15.9"x17.5"x18.5" | 15.9"x18.7"x18.7" | 15.9"X20.8"X18.5" | 15.9"x17.5"x18.5" | 15.9"x18.7"x18.7" |
| Box Weight | 27.5lbs | 32lbs | 30.6lbs | 28.5lbs | 33lbs |
| Box Dimensions | 19.3"x18.7"x17.1" | 20.3"x20.3"x17.1" | 21.1"X19.3"X16.9" | 19.3"x18.7"x17.1" | 20.3"x20.3"x17.1" |
| Safety Certification | ETL/CETL | ETL/CETL | - | ETL/CETL | ETL/CETL |
| | | | | | |

LED and Standard Vertical Advertisement Blowers 12"

| MODEL NO. | BR-18L | BR-430 | BR-430L | BR-440 | BR-440L |
|----------------------|------------------|-------------------|-------------------|-------------------|-------------------|
| VOLTS/HERTZ | 120V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz |
| MOTOR | 1/7HP | 1/3HP | 1/3HP | 1/3HP | 1/3HP |
| POWER | 0.92A | 4.2A | 4.2A | 4.2A | 4.2A |
| RATED AIRFLOW | 160CFM | 3200CFM | 3200CFM | 3200CFM | 3200CFM |
| SPEED | SINGLE | 1 SPEED | 1 SPEED | 1 SPEED | 1 SPEED |
| CORD LENGTH | 10' | 15' | 15' | 15' | 15' |
| UNIT WEIGHT | 9.3lbs | 15lbs | 16.3lbs | 16.1lbs | 17.4lbs |
| UNIT DIMENSIONS | 20.9"x20.1"x6.7" | 14.8"x14.8"x13.1" | 14.8"x14.8"x16.2" | 14.8x14.8"x13.1" | 14.8"x14.8"x16.2" |
| BOX WEIGHT | 12.3lbs | 17.1lbs | 18.4lbs | 18.2lbs | 19.5lbs |
| BOX DIMENSIONS | 20.9"x20.1"x7.7" | 15.2"x15.2"x13.8" | 15.2"x15.2"x17.1" | 15.2"x15.2"x17.1" | 15.2"x15.2"x17.1" |
| SAFETY CERTIFICATION | - | - | - | ETL/CETL | ETL/CETL |
| | | | | | |

Vertical Advertisement Blowers 18"

| MODEL NO. | BR-450 | BR-450L | BR-460 | BR-460L |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| VOLTS/HERTZ | 115V/60Hz | 115V/60Hz | 115V/60Hz | 115V/60Hz |
| MOTOR | 1HP | 1HP | 1HP | 1HP |
| POWER | 8.3A | 8.3A | 8.3A | 8.3A |
| RATED AIRFLOW | 5800CFM | 5800CFM | 5800CFM | 5800CFM |
| SPEED | 2 SPEED | 2 SPEED | 2 SPEED | 2 SPEED |
| CORD LENGTH | 15' | 15' | 25' | 25' |
| UNIT WEIGHT | 32.2lbs | 34lbs | 32.2lbs | 34lbs |
| UNIT DIMENSIONS | 19"x19.7"x17.7" | 19"x19.7"x19.1" | 19"x19.7"x17.7" | 19"x19.7"x19.1" |
| BOX WEIGHT | 36.8lbs | 38.4lbs | 36.8lbs | 38.4lbs |
| BOX DIMENSIONS | 20"x19.9"x16.1" | 20"x20"x17.7" | 20"x19.9"x16.1" | 20"x20"x17.7" |
| SAFETY | - | - | ETL/CETL | ETL/CETL |
| CERTIFICATION | | | | |

14 www.xpower.com

Air Pumps

| MODEL NO. | AP-1031A | AP-1131 | AP-138A | AP-145A |
|---------------------------|-------------------|-------------------|-------------------|------------------|
| POWER SOURCE | AC-Electric | DC-Car Plug | AC | AC |
| POWER | 120V/60Hz | 12V | 120V/60Hz | 120V/60Hz |
| AMP | 1.7A | 6A | 2.3A | 10.0A |
| PSI | 1.00 | 1.00 | 1.50 | 4.00 |
| POWER CORD LENGTH | 5' | 6' | 5' | 5' |
| VALVE ADAPTERS | 3 | 3 | 2 | 3 |
| UNIT DIMENSIONS | 4"x3.5"x5" | 4"x3.5"x5" | 7.9"x4.8"x5.4" | 9.4"x7.5"x8.5" |
| UNIT WEIGHT | 1.09 lbs. | 0.77 lbs. | 1.6 lbs. | 4.2 lbs. |
| INNER BOX SIZE | 4.9"x3.9"x5.3" | 4.9"x3.9"x5.3" | 8.5"x5.3"x5.7" | 10"x8.9"x7.9" |
| INNER BOX WEIGHT | 1.22 lbs. | 0.93 lbs. | 1.82 lbs. | 4.64 lbs |
| NO. UNITS PER MASTER PACK | 24 | 24 | 12 | 4 |
| MASTER PACK DIMENSIONS | 16.5"x15.6"x11.4" | 16.5"x15.6"x11.4" | 17.7"x16.7"x12.2" | 20.9"x18.5"x8.7" |
| MASTER PACK WEIGHT | 31.08 lbs. | 24.16 lbs | 23.6 lbs | 20.30 lbs. |
| ADDITIONAL FEATURES | M / A / - / / / / | - | | 3.2' flex hose |
| SAFETY CERTIFICATION | UL/CUL | - | UL/CUL | - |
| | | | | |

Air Pumps

| MODEL NO. | AP-123 | AP-122A+ | AP-1138 | AP-142A |
|---------------------------|-----------------------------------|-----------------------------|--------------------|----------------------|
| POWER SOURCE | 4 "D" Batteries (not included) | AC/DC-Car Plug 120V/60Hz | DC Car Plug 12V | AC 120V/60Hz |
| POWER | 6V | +12V Charger | N/A | 4.2 Amps |
| AMP | N/A | N/A | 1.00 | 2.30 |
| PSI | 0.50 | 0.50 | 6' | 5' |
| POWER CORD LENGTH | n/a | 6' AC/3.6' DC | 2 | 3 |
| VALVE ADAPTERS | 3 | 3 | 7.87"x4.8"x5.39" | 7.24"x4.17"x5.35" |
| UNIT DIMENSIONS | 4.55"x4.15"x4.55" | 3.85"x3.35"x3.95" | 1.2 lbs. | 2.2 lbs. |
| UNIT WEIGHT | 0.6 lbs. | 0.9 lbs. | 8.46"x5.31"x5.71" | 8.46"x5.31"x6.5" |
| INNER BOX SIZE | 5.35"x4.75"x5.15" | 4.7"x4.7"x4.1" | 1.4 lbs. | 2.4 lbs. |
| INNER BOX WEIGHT | 0.8 lbs. | 1 lbs. | 12 | 12 |
| NO. UNITS PER MASTER PACK | 24 | 24 | 17.5"x16.54"x12.4" | 17.52"x16.54"x13.58' |
| MASTER PACK DIMENSIONS | 19.7"x16.75"x11.6" | 19.7"x15"x9.1" | 18.74 lbs. | 30.36 lbs. |
| MASTER PACK WEIGHT | 19.80 lbs. | 26.20 lbs. | - | 3.2' flex hose |
| ADDITIONAL FEATURES | - | - | - | - 4 / / |
| SAFETY CERTIFICATION | - | UL/CUL | - | - |
| | | | | |

Air Pumps

| MODEL NO. | AP-126A+ | AP-139A+ | AP-149A+ | AP-1395A+ | AP-1495A+ |
|----------------------|---------------------|---------------------|-----------------------------|---------------------|-----------------------------|
| POWER SOURCE | AC/DC+ | AC/DC + | AC/DC+ | AC/DC + | "AC/DC+ |
| FOWER SOURCE | Rechargeable | Rechargeable | Rechargeable | Rechargeable | Rechargeable |
| POWER | Battery | Battery | Battery | Battery | Battery" |
| PSI | 120V/60Hz | 120V/60Hz | 120V/60Hz | 120V/60Hz | 120V/60Hz |
| POWER CORD LENGTH | +12V Charger | +6V Charger | +12V Charger | + 12V Charger | + 12V Charger |
| VALVE ADAPTERS | 0.55 | 0.65 | 0.65 | 1.00 | 1.00 |
| UNIT DIMENSIONS | 6' AC/3.6' DC | 6' AC/3.6' DC | 6' AC/3.6' DC | 6' AC/3.6' DC | 6' AC/3.6' DC |
| UNIT WEIGHT | 3 | 2 | 3 | 2 | 3 |
| INNER BOX SIZE | 4.35"x3.85"x4.20" | 9.15"x4.05"x6.15" | 9.65"x4.53"x6.5" | 9.13"x4.06"x6.14" | 9.65"x4.53"x6.5" |
| INNER BOX WEIGHT | 1 lbs. | 2.8 lbs. | 3.7 lbs. | 3.8 lbs. | 4 lbs. |
| NO. UNITS PER MASTER | 4.72"x4.72"x4.92" | 9.45"x4.72"x6.89" | 9.84"x6.3"x7.09" | 9.45"x4.72"x6.85" | 9.84"x6.3"x7.09" |
| PACK | 1.1 lbs. | 3 lbs. | 4.1 lbs. | 4.1 lbs. | 4.4 lbs. |
| MASTER PACK | 24 | 12 | 6 | 12 | 6 |
| DIMENSIONS | 19.7"x16.75"x11.85" | 19.9"x14.96"x14.96" | 19.49"x10.43"x14.76" | 19.9"x14.96"x14.96" | 19.49"x10.43"x14.76 |
| MASTER PACK WEIGHT | 29.30 lbs. | 39.80 lbs. | 26.20 lbs. | 51.70 lbs. | 27.50 lbs. |
| ADDITIONAL FEATURES | - | - | 3.3' flex hose LED Light | 3.3' flex hose | 3.3' flex hose LED Light |
| SAFETY CERTIFICATION | UL/CUL | UL/CUL | UL/CUL | UL/CUL | UL/CUL |
| | | | | | |

Jan/San - Restoration



Inflatable Blowers



Air Pumps















