



X-2700

PROFESSIONAL 3-STAGE HEPA AIR SCRUBBER

Designed with the unique needs of professional restoration, contractors, and other cleaning professionals, the XPOWER X-2700 3-Stage Professional HEPA filtered air purifier gives you maximum options with 5 speeds and 550 CFM airflow capacity. Advanced digital controls for speed settings, a timer function, and a PM2.5 air quality meter make it the most user-friendly, easy-to-set-up air scrubber on the market, and the timer makes off-hours operation a breeze. Suitable for a variety of applications in spaces where optimal indoor air quality and maximum air exchange rate is needed, the X-2700 is suited for all your jobsite/project needs. Capable of ducting inlet and exhaust points, makes this unit easy to setup for Positive and Negative air applications. Developed to restore indoor air quality at a variety of job sites—the X-2700 with HEPA filter effectively removes contaminants such as bacteria, allergens, mold and sub-micron sized dust with its advanced 3 stage filtration technology.

- Commercial performance with a compact portable size perfect for all job sites
- Digital Control Panel for Timer Function, Filter light indicator, 5 Speed Settings



XPOWER MANUFACTURE, INC
668 S 6TH AVE CITY OF INDUSTRY, CA 91746
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM

WWW.XPOWER.COM

SPECIFICATIONS

- Digital PM2.5 Air Quality sensor with built-in read out and light indicator
- Timer function for easy set and forget air purification; perfect to setup during off hours
- Powerful and energy efficient 1/2 HP external rotor induction motor
- Low 2.8 Amp draw with 550 CFM maximum airflow capacity
- 5-speed digital control panel for Powerful high-speed to an extremely quiet low-speed
- 3-stage filtration system including HEPA filters + washable easy maintenance nylon filter and pleated media filter for extended HEPA filter life
- Stackable, lightweight, and compact design constructed of durable ABS plastic
- Filter change indicator light, tool-less filter changes
- Duct-able intake/exhaust mouth for Negative & Positive Air applications

MODEL NO.	X-2700
VOLTS/HERTZ	115V / 60Hz
MOTOR	1/2 HP
MAX AMP	2.8 A
RATED AIRFLOW	550 CFM
SPEEDS	5 Speed
CORD LENGTH	13 ft.
STACKABLE	Yes
UNIT WEIGHT	23.7 Lbs.
UNIT DIMENSIONS (LXWXH)	16.6" x 10.4" x 18.9"
HOUSING	ABS
DUCT SIZE (AIR OUTLET DIMENSIONS)	6 x 11.9 inch.
DUAL THERMAL PROTECTION	Yes
PALLET QUANTITY	32

FEATURES



Digital Control Panel



PM2.5 Air Quality Display Panel



Stackable

3 STAGE FILTRATION SYSTEM



NFS13
WASHABLE NYLON MESH FILTER




PF13
PLEATED MEDIA FILTER



HEPA65-33
HEPA FILTER

FILTER CHANGE LIGHT Indicates when filter needs to be cleaned or changed.



Standards for the Workplace.