



# 80 SERIES XPOWER AIR MOVER

## Ventilate and Dry Like a Pro

The XPOWER P-80 and P-80A Mini Mighty Air Movers deliver powerful airflow of up to 600 CFM with an efficient 138-watt motor. Drawing only 1.2 Amps at the highest speed setting, these multipurpose air movers are must-have additions for your home or garage.

Built with rugged, state-of-the-art injection mold technology, these compact yet mighty air movers are perfect for drying tight crawl spaces, beneath kitchen counters, inside cabinets, bathrooms, auto interiors, and more. Both models feature a three-speed switch for full airflow control, a stackable design for easy storage, and convenient wraparound cord storage.

While the P-80 weighs less than 7 pounds, the P-80A—equipped with onboard power outlets for daisy-chaining multiple units—comes in at under 10 pounds. Whether for home, garage, or professional use, the XPOWER Mini Mighty Air Movers are designed for efficiency, durability, and portability.

- Powerful and energy efficient 138 W induction motor
- Low 1.2A draw with 600 CFM max. airflow capacity
- 3 speeds with 4 Positions (0°, 20° kickstand, 45° & 90°)
- Stackable up to 4 units high for easy storage
- Lightweight, compact and durable polypropylene (PP) plastic housing design
- P-80A has a built-in power outlets for daisy chain with dual thermal protection



**XPOWER MANUFACTURE, INC**  
688 S 6TH AVE, CITY OF INDUSTRY, CA 91746  
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM

[WWW.XPOWER.COM](http://WWW.XPOWER.COM)

# SPECIFICATIONS

|                                |                                 |                                 |
|--------------------------------|---------------------------------|---------------------------------|
| <b>Model No.</b>               | P-80A                           | P-80                            |
| <b>Volts/Hertz</b>             | 115 V / 60 Hz                   | 115 V / 60 Hz                   |
| <b>Motor</b>                   | 138 W                           | 138 W                           |
| <b>Power</b>                   | 1.2 Amps                        | 1.2 Amps                        |
| <b>Rated Airflow</b>           | 600 CFM                         | 600 CFM                         |
| <b>Speed</b>                   | 3 Speeds                        | 3 Speeds                        |
| <b>Cord Length</b>             | 10 Ft.                          | 10 Ft.                          |
| <b>Operating Positions</b>     | 4 Positions (0°, 20°, 45°, 90°) | 4 Positions (0°, 20°, 45°, 90°) |
| <b>Stackable</b>               | Yes                             | Yes                             |
| <b>Daisy Chain</b>             | Yes                             | No                              |
| <b>Unit Weight (Lbs.)</b>      | 7.9 Lbs.                        | 6.6 Lbs.                        |
| <b>Unit Dimensions (LxWxH)</b> | 11.5 x 9.3 x 12.3 inch.         | 11.5 x 9.3 x 12.3 inch.         |
| <b>Box Weight (Lbs.)</b>       | 9.5 Lbs.                        | 8.2 Lbs.                        |
| <b>Box Dimensions (LxWxH)</b>  | 12.6 x 11.8 x 9.8 inch.         | 12 x 9.8 x 12.6 inch.           |
| <b>Housing</b>                 | PP                              | PP                              |
| <b>Safety Certification</b>    | ETL/CETL                        | ETL/CETL                        |
| <b>Dual Thermal Protection</b> | Yes                             | Yes                             |
| <b>Pallet Quantity</b>         | 84                              | 84                              |



## FEATURES

### 4 Operating Positions

