



Energy Efficient, Powerful & Versatile

Professional Air Movers

The 400 Series is available with either rugged ABS or lighter weight polypropylene (PP) housing. Professionals will also appreciate the daisy chain feature available on selected models. It is precision manufactured using state-of-the-art technology to ensure superior performance.

For the following applications, the 400 Series offers both quality and economy when used drying the following:

- Carpets and area rugs
- Hardwood floors
- Basements
- Cellars
- Ceilings and walls
- Bathrooms
- Ceramic tile

As a ventilation device, the 400 Series is a reliable work horse and can be utilized in 4 positions - 0, 20, 45 and 90 degrees. With its low 3A power draw and 1600 CFM rated airflow at top speed, it will do its job quickly and efficiently.

Additional features that distinguish the 400 Series from competitive air movers include:

- Stackability
- Daisy chain (optional)
- 3 Speeds
- Light weight

The 400 Series is ETL/CETL safety certified globally.



P-400



X-400



X-400A



XPOWER MANUFACTURE, INC. • 220 CLARY AVENUE, SAN GABRIEL, CA 91776 • www.XPOWER.com PHONE: (626) 285-3301 • FAX: (626) 285-3302 • EMAIL: info@XPOWER.com

SPECIFICATIONS

Air Mover Series	400 Series		
Model No	P-400	X-400	X-400A
Volts/Hertz	115V/60Hz		
Motor	1/4 HP	1/4 HP	1/4 HP
Power	3A	3A	3A
Rated Airflow	1600 CFM	1600 CFM	1600 CFM
Speeds	3 Speed		
Cord Length	20 ft.		
Operating Position	4 Positions (0°, 20°, 45°, 90°)		
Daisy Chain			1
Filter Kit	OPTIONAL		
Stackable	*	1	✓
Unit Weight	15 lbs	16 lbs	17.2 lbs
Unit Dimensions (LxWxH)	13.9"x14.8"x14.6"	13.9"x14.8"x14.6"	13.9"x14.8"x14.6"
Box Weight	19 lbs	20 lbs	21.2 lbs
Box Dimensions (LxWxH)	15.5"x15"x15.2"	15.5"x15"x15.2"	15.5"x15"x15.2"
Housing	PP	ABS	
Safety Certification	ETL/CETL		
Dual Thermal Protection	1	1	✓
Pallet Qty	45	45	45

