









XD-85L2

LGR DEHUMIDIFIER

The XPOWER XD-85L2 Large Capacity LGR Dehumidifier is the latest in Advanced Water Damage Restoration Technology. With a patented Dual Intake System design, the XD-85L2 has become the most efficient and highest output Low Grain Refrigerant Dehumidifier in its class.

Boasting 85 PPD @ AHAM (80°F / 60% RH), this LGR Dehumidifier draws 6.7 amps and includes all the features you have come to expect from a professional grade manufacturer. An easy navigating digital display, smart controls, integrated handles, and self-purging water pump all come standard on this unit. Also standard and included are the following features: folding handle for easy storage and transporting, secure stacking capability, integrated storage compartment for power cord and drain hose, and easy ducting outlet. This 67 LB 180 CFM powerhouse LGR Dehumidifier is the investment that offers the strongest ROI and performance restorers will appreciate.

XACTIMATE Code: WTRDHM>L

Commonly used in drying applications, but not limited to:


- Water Damage Restoration
- Carpet Cleaning / Hotel Hospitality
- Construction / Plumbing
- · Hardwood Floors / Textiles
- · Crawl Space / Attics
- · Basements / Cellars
- · Kitchens / Food Preparation Stations




SPECIFICATIONS



XD-85L2 MODEL NO. WATER REMOVAL EFFICIENCY AT 85 Pints Per Day AHAM (80 °F / 60% RH) WATER REMOVAL AT 145 Pints Per Day FULL SATURATION (90°F / 90% RH) VOLTS/HERTZ 115 V~60 Hz **POWER** 6.7 A RATED AIRFLOW 180 CFM **SPEEDS Automatic Speed** Stainless-Steel Filter FILTER TYPE PΕ HOUSING 10 Ft. **CORD LENGTH DRAIN HOSE LENGTH** 40 Ft. Up to 9999 hours **TIME METER** 50 minutes 33°F - 105°F **OPERATING RANGE UNIT WEIGHT** 70.5 Lbs. **UNIT DIMENSIONS (LXWXH)** 13.1 x 32.2 x 22.5 in ETL / CETL **SAFETY CERTIFICATIONS** 18 **PALLET QUANTITY**



Relative Humidity Display Total Running Time





FEATURES



Folding Handle

Fahrenheit/Celsius Scale Switch

Stabilized Stacking

Wheels for Easy Transport

Stackable