



**BED BUG CONTROL
the Red Hot Opportunity**

Building service contractors, property management agencies, as well as independent hotel/motel owners are pairing XPOWER Heat Resistant Axial Fans with heating equipment designed specifically for bed bug remediation for optimum result.

X-48ATR

HIGH TEMPERATURE AIR MOVERS

The XPOWER X-48ATR is a high temperature fan that can withstand room temperatures up to 180 degrees Fahrenheit and can be used in conjunction with radial heaters to circulate hot air. Great for pest control and water damage restoration applications. Use this high performance fan with its unique grill design to extend a powerful and focused stream of air up to 60 ft. in any direction. The X-48ATR also features a sealed motor to protect it from contaminants and water damage. Easily transportable, this super lightweight fan can be stacked up to 5 units high.

**HI-TEMP
RESISTANT** 180°F



Up to **30%
More
Efficient**

**SEALED
MOTOR**
To Resist Corrosion

**3-HOUR
TIMER**
Set & Forget



Why XPOWER products:

- Designed for high temperature work environs up to 180°F / 80°C
- Great for pest control and water damage restoration applications
- Features a SEALED Motor to Protect it from Contaminants and Water Damage
- Low 2.8 Amps Draw with 3600 CFM Max. Airflow Capacity
- Rack/stand Included Allowing 360-Degree Rotation
- Lightweight & Stackable up to 5 units high for Easy Storage




XPOWER MANUFACTURE, INC
240 CLARY AVENUE, SAN GABRIEL, CA 91776
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM


WWW.XPOWER.COM

SPECIFICATIONS


AIRFLOW DIAGRAMS




External roto-motor and front grill design creates focused air flow that travels up to 160ft



Bounce the air off of walls in smaller rooms so air reaches every corner



Constantly recirculates air to create a gentle and consistent stream of air flow to shorten drying time



Point it downward to dry area around the fan up to 80 ft in diameter

MODEL NO.	X-35AR
VOLTZ/HERTZ	115V / 60 Hz
MOTOR	1/3 HP
POWER	2.8 Amps
RATED AIRFLOW	3600 CFM
SPEED	Variable Speed
CORD LENGTH	20 Ft.
OPERATING POSITION	360 Degree
STACKABLE	5 Units
UNIT WEIGHT	25.6 Lbs.
UNIT DIMENSIONS (LxWxH)	21.9 x 9.8 x 22.5 in.
HOUSING	ABS+PC
SAFETY CERTIFICATIONS	ETL / CETL
DUAL THERMAL PROTECTION	Yes
PALLET QUALITY	28 Units

FEATURES

360° Rotation



Adjustable Rack



Built in Power Outlet



Stackable



PRODUCT FEATURES

Auxiliary Outlet with Circuit Breaker for Daisy Chain

Variable Speed Control Switch & 3 Hour Timer

Sealed Motor that Produces Efficient, Powerful and Quiet Airflow

Durable ABS or ABS+PC Housing Design

Quick Release Knob for Easy Angle Adjustment

Rack / Stand Allowing 360° Angle Rotation

