



POWERFUL, EFFICIENT, COMPACT + LIGHTWEIGHT









The XPOWER line of axial fans are easily the most compact and versatile axials available to the restoration market today. Weighing between 10-23 Lbs., every PERFORMANCE PROVEN axial produces LARGE volumes of CFM to efficiently dry out any size water loss. With amp draws below 2.8, restorers can confidently and safely daisy chain as many as 4 units on a single circuit with the 2 on-board power receptacles.

Every unit comes with a removable full-range 360° adjustable stand and features powerful drying and ventilating functionality. A specially designed housing has the capability to direct airflow upwards to 190 feet. These lightweight, stackable axial fans will improve your efficiency and profitability.

- Low Amp Draw, Large CFM
- On-board power receptacles to daisy chain
- 4-Speed / Variable speed control
- Specially designed housing extends airflow up to 190 ft.
- Removable 360° full-range adjustable stand
- Lightweight & Stackable for easy transport & storage



SPECIFICATIONS

MODEL NO.	P-21AR	P-26AR	X-39AR	X-47ATR
VOLTZ/HERTZ	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz
MOTOR	69 W	115 W	1/4 HP	1/3 HP
POWER	0.6 A	1 A	1.6 A	2.8 A
RATED AIRFLOW	1100 CFM	1300 CFM	2100 CFM	3600 CFM
SPEEDS	4 Speed	4 Speed	Variable Speed	Variable Speed
CORD LENGTH	10 Ft.	10 Ft.	20 Ft.	20 Ft.
OPERATING POSITIONS	360° Rotation (Rack Included)	360° Rotation (10" Rack Included)	360° Rotation (Rack Included)	360° Rotation (10" Rack Included)
STACKABLE	Yes	Yes	Yes	Yes
3 HOUR TIMER	No	No	No	Yes
DAISY CHAIN	Yes	Yes	Yes	Yes (GFCI)
UNIT WEIGHT	10.4 Lbs.	11.7 Lbs.	16.7 Lbs.	22.2 Lbs.
UNIT DIMENSIONS (LXWXH)	16.1 x 4.2 x 8.9 in.	17.3 x 15.4 x 8.9 in.	18.6 x 9.4 x 19.2 in.	21.9 x 9.8 x 22.5 in.
HOUSING	ABS	ABS	ABS	ABS
SAFETY CERTIFICATIONS	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL
DUAL THERMAL PROTECTION	Yes	Yes	Yes	Yes
PALLET QUANTITY	72 Units	48 Units	42 Units	28 Units

AIRFLOW DIAGRAMS



Extermal roto-motor and front grille design creates focused air flow that travels up to 190ft



Bounce the air off of walls is smalle



Constantly recirculats air to create a gentle and consistent stream of air flow to shorten drying time



Auxiliary Outlet with Circuit Breaker for Daisy Chain



Sealed Motor that Produces Efficient, Powerful and Quiet Airflow

Specially Designed Air Fin Guide for More Focused & Extended Airflow Range Up to 190 ft.

> Stand Alone Design with Rubber Footing that Works Even With/without Rack

PRODUCT FEATURES





3-Hour Timer & Variable Speed Control Switch

Durable ABS or ABS+PC Housing Design

Quick Release Knob for Easy Angle Adjustment

Wrap Around Cord Design

Fully Installed Rack / Stand Allowing 360° Angle Rotation

ACCESSORIES:











