



VIKING PDS-PRO

Pressurized Wall Cavity Dryer



The VIKING PDS-Pro System by XPOWER Manufacture is the next evolution of the PDS line of wall cavity dryers. The PDS-Pro features advancements in the PDS line with a new digital screen with independent heating and air flow controls. The PDS-Pro now offers Variable HEAT via it's built-in heater element. High CFM airflow is now produced with a brushless motor (rated at 10.5 amps) and advance digital variable speed control. Long maintenance free motor life, rated at over 5,000+ hrs. This means, No more brush changes, ever!

You can easily set up the system for drying multiple walls, cabinets, ceilings, and other creative options to maximize your drying efforts. COME DRY WITH US!



XPOWER MANUFACTURE, INC
668 S 6TH AVE CITY OF INDUSTRY, CA 91746
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM

WWW.XPOWER.COM

SPECIFICATIONS

- Pressurized heated airflow for optimal wall cavity drying
- PDS-Pro rated at 10.5 Amps with brushless motors
- No more brush changes and long motor life rated at 5,000+Hrs
- Kit includes wall drying kit (PDS-WDK)
- Wall Drying Kit includes: (1) 3-Way Main Nozzle connector, (4) 6' Main Hose kits, 100ft yellow injector tubing, (50) wall injector nozzles, (6) end caps, (5) main hose connectors, and (8) main hose cuffs
- Digital display screen with optimized speed and heat settings
- Variable speed control for continued drying on occupied dries
- Variable heat controller with built-in heater element for advance heating control options
- Injection nozzles with an easy setup design enhance efficiency by simplifying both the setup and takedown processes.
- One 1 PSI pressure release valve maintains consistent drying capability
- Built-In Cord Wrap for easy storage without messy cords hanging

MODEL NO.	PDS-Pro
VOLTZ/HERTZ	115V / 60 Hz
MOTOR	4 HP
POWER	10.5 Amps
RATED AIRFLOW	150 CFM
SPEEDS	Variable Speed
CORD LENGTH	10 Ft.
TUBING	Yellow Tubing (100 Ft.)
OPERATING TEMPERATURE	Up to 100F
UNIT WEIGHT	23.1 Lbs.
UNIT DIMENSIONS (LxWxH)	17.2 x 6.3 x 9.8 in.
HOUSING	ABS
SAFETY CERTIFICATIONS	ETL
PALLET QUANTITY	14 Units



ON/OFF Switch With Variable Speed & Heat Control



3-Way Main Nozzle Air Pressure Control Valve